

02 0264





Quicklock circular connectors, IP67



Quicklock socket, IP67, size 28, straight version, with plastic housing and screw clamps

Approvals:  02/03 poles

02 0264



0264 02

0264 03

Environmental conditions

Temperature range -40 °C/+80 °C

Materials

Insulating body PBT, V-0 according to UL94
 Contact bush CuZn, gold-plated
 Housing PBT, V-0 according to UL94¹
 Guiding element Zn alloy, chrome-plated
 Cap nut PBT, V-0 according to UL94¹

¹ outdoor sustainable (F1 according to UL 746C)

Mechanical data

Mating cycles 1700
 Insertion force ≤ 90 N
 Withdrawal force ≤ 40 N
 Protection class IP67¹

¹ only in locked condition with an appropriate counterpart

Connectable conductors for screw clamp

Section 2.5–16.0 mm²/AWG 14–6
 Cable diameter 4.0–11.5 mm

Electrical data (at T_{amb} 20 °C)

Contact resistance ≤ 5 mΩ
 Rated current 50 A (2 poles)
 43 A (3 poles)
 Rated voltage 500 V AC
 Rated impulse voltage ≤ 2500 V
 Creepage distance ≥ 2 mm
 Clearance ≥ 2 mm
 Insulation resistance > 500 MΩ

Associated products

Counterparts
 ☞ 0254

02 0264

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
0264 02	2	2	20
0264 03	3	2	20

Packaging:

in individual plastic bags, in a cardboard box