

03 0385


Circular connectors with threaded joint M16 acc. to IEC 61076-2-106, IP40/IP68



Slit nut for chassis plugs and sockets (spare part)

03

0385



Environmental conditions

Temperature range -40 °C/+85 °C

Mechanical data

Tightening torque nut 1-3 Nm

Associated products

Accessories

☞ 030398	☞ 0304	☞ 0304-1
☞ 0304-2	☞ 0305	☞ 0305-1
☞ 0305-1 U	☞ 0305-2	☞ 0306
☞ 0306-1	☞ 0306-2	☞ 0307
☞ 0307-1	☞ 0307-2	☞ 030798-1
☞ 030798-2	☞ 030799-2	☞ 0314
☞ 0314-1	☞ 0314-2	☞ 0315
☞ 0315-1	☞ 0315-1 U	☞ 0315-2
☞ 0316	☞ 0316-1	☞ 0316-2
☞ 0317	☞ 0317-1	☞ 0317-2
☞ 031798-1	☞ 031798-2	☞ 031799-2
☞ 0362	☞ 0363	☞ KFR
☞ KFV	☞ KFV ... C	☞ KGR
☞ KGV	☞ KGV ... C	☞ SFV
☞ SFV ... C	☞ SGR	☞ SGV
☞ SGV ... C		

Harnessing equipment

[☞ ZMS 20](#)

03

0385

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
0385	-	100	500

Packaging:

in a cardboard box