


35

352300

RAST 2.5 connectors, pitch 2.5/5.0 mm




RAST 2.5 plus™ connector for direct and indirect mating,
with double-sided keying, insulation displacement
technology (IDT), consecutive placement without loss of
pitch
contact pitch 5.0 mm

Approvals:



35 352300



- *a terminated connector
- *b K = keying
P = Positioning
- *c chaining of the component parts (state of delivery)


Environmental conditions

Temperature range -40 °C/+130 °C¹
¹ upper limit temperature (insulating body) RTI (electrical) of the UL Yellow Card


Materials

Insulating body PA, V-0 according to UL94¹
 Contact spring CuSn, tin-plated
¹ material halogen-free, GWFI 850 °C, GWIT 775 °C

Mechanical data

Mating with printed circuit board 1.5 ± 0.14 mm
 Insertion force/contact ≤ 4,0 N
 Withdrawal force/contact ≥ 0,5 N
 Keying proposals at www.lumberg.com 









Connectable conductors for IDT area


Construction discrete conductor, notched flat cable 2.5 mm
 Section min. 0,35 mm²
 Section max. 0,38 mm²
 Insulation diameter ≤ 1,6 mm
 Approved cables at www.lumberg.com 

Electrical data (at T_{amb} 20 °C)

Contact resistance ≤ 5 mΩ
 Rated current 4 A (T_{amb} 60 °C)
 2 A (T_{amb} 100 °C)
 Rated voltage 250 V AC
 Material group I (IEC)/0 (UL) (CTI ≥ 600)
 Creepage distance 3,65 mm
 Clearance 3,20 mm
 Insulation resistance > 1 GΩ

Associated products

Counterparts
 3542  3542-1  3546
 3546-1  3552  355295
 355299  3556  83546

Accessories
 3500

Harnessing equipment

- [HA3...e](#)
 - [HA35 plus](#)
 - [HZ35-K](#)
 - [KHP35 plus](#)
 - [VARICON 7000](#)
 - [VARICON 7000-Eco](#)
 - [VARICON 7000-Eco-CR](#)
 - [VARICON 7000-Inline](#)
 - [VARICON 7000-Inline-CR](#)
 - [VARICON 7000-RD](#)
-

35

352300

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)	Dimensions	
				A (mm)	B (mm)
352300 02	2	3456	10368	5.0	9.9
352300 03	3	2160	10800	10.0	14.9
352300 04	4	1728	5184	15.0	19.9
352300 05	5	1296	3888	20.0	24.9
352300 06	6	864	2592	25.0	29.9

Designation to be completed by further details (e.g. for keying, color or material options).

Packaging:

chained, in a cardboard box