

45 458000 01

High-current contact elements




High-current contact bush, in through hole technology (THT), mateable from top, bottom or lateral direction, for tab contacts 0.5–0.8 mm, for printed circuit boards

Approvals:

LV215

VW
80332

45 458000 01



Environmental conditions

Temperature range -40 °C/+125 °C

Materials

Contact CuCr alloy, tin-plated

Mechanical data

Mating with tab contact 2.8–6.8 mm x 0.5 mm – 458000 01 0,5
tab contact 2.8–6.8 mm x 0.6 mm – 458000 01 0,6
tab contact 2.8–6.8 mm x 0.8 mm – 458000 01 0,8
applicable for reflow soldering on printed circuit board
applicable for laser welding on a busbar or lead frame

Mating cycles ≤ 5

Insertion force
tab 0.5/0.6 mm
25 N ± 15 N – top/bottom entry
18 N ± 10 N – lateral entry
tab 0.8 mm
35 N ± 15 N – top/bottom entry
18 N ± 10 N – lateral entry¹

Withdrawal force
tab 0.5/0.6 mm
25 N ± 12 N – top/bottom entry
15 N ± 10 N – lateral entry
tab 0.8 mm
35 N ± 10 N – top/bottom entry
15 N ± 10 N – lateral entry¹

¹ measured with a tin-plated test tab

Electrical data (at T_{amb} 20 °C)

Contact resistance < 1 mΩ

Rated current ≤ 56 A¹


¹ depending on the connection to the printed circuit board, installation situation and heat dissipation

Associated products

Counterparts







☞ 459000 0,8 1275 ☞ 459010 0,8 1260 ☞ 459010 0,8 1800
☞ 459020 0,8 1700 ☞ 459120 0,8 2000

45 458000 01



45


458000 01




45

458000 01


Assembly tolerances for top and bottom entry
- tab dimensions 4.8 mm x 0.5/0.6/0.8 mm x length 8 mm
- larger assembly tolerances possible for lengths > 15 mm




typical mating




permissible lateral offset



permissible tilt



permissible twist



permissible combined tolerances


45 458000 01

Assembly tolerances for lateral entry


- tab dimensions 4.8 mm x 0.5/0.6/0.8 mm x length 8 mm
- larger assembly tolerances possible for lengths > 15 mm




typical mating




permissible lateral offset



permissible tilt




permissible twist



permissible combined tolerances



45 458000 01

Geometry of the mating tab contact




Material to be coordinated with Lumberg.

Packaging 458000 01 ...VP12
reel: 330 mm/100 mm/24.5 mm
leader: 408 mm, 34 empty cavities
trailer: 168 mm, 14 empty cavities



Packaging 458000 01 ...VP26
additionally with adhesive film as suction
surface for automatic placement



45

458000 01

-
- *a THT solder pin
 - *b contact point
 - *c mating from top direction
 - *d mating from lateral direction
 - *e mating from bottom direction
 - *f printed circuit board layout (example) for mating from top or lateral direction
 - *g printed circuit board layout (example) for mating from top or bottom direction
 - *h bore hole for THT solder pin
 - *i slot in the printed circuit board min. 0.5 mm wider than tab
 - *k contact tab
 - *l printed circuit board
 - *m dimension 1.5 mm depending on the slot in the printed circuit board
 - *n insertion depth

45 458000 01

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
458000 01 0,5 V12VP12	1	4000	
458000 01 0,6 V12VP12	1	4000	
458000 01 0,8 V12VP12	1	4000	
458000 01 0,8 V12VP26	1	4000	

Packaging:
on reel