

45 458002 01

High-current contact elements




High-current contact bush, in surface mount technology (SMT), mateable from top, bottom or lateral direction, for tab contacts 0.5–0.8 mm, for printed circuit boards or busbars

Approvals:

LV215

VW
80332

45 458002 01



Environmental conditions

Temperature range -40 °C/+125 °C

Materials

Contact CuCr alloy, tin-plated

Mechanical data

Mating with tab contact 2.8–6.8 mm x 0.5 mm – 458002 01 0,5
tab contact 2.8–6.8 mm x 0.6 mm – 458002 01 0,6
tab contact 2.8–6.8 mm x 0.8 mm – 458002 01 0,8
applicable for reflow soldering on printed circuit board
applicable for laser welding on a busbar or lead frame

Mating cycles ≤ 5

Insertion force tab 0.5/0.6 mm
25 N ± 15 N – top/bottom entry
18 N ± 10 N – lateral entry
tab 0.8 mm
35 N ± 15 N – top/bottom entry
18 N ± 10 N – lateral entry¹

Withdrawal force tab 0.5/0.6 mm
25 N ± 12 N – top/bottom entry
15 N ± 10 N – lateral entry
tab 0.8 mm
35 N ± 10 N – top/bottom entry
15 N ± 10 N – lateral entry¹

¹ measured with a tin-plated test tab

Electrical data (at T_{amb} 20 °C)

Contact resistance < 1 mΩ

Rated current ≤ 56 A¹

¹ depending on the connection to the printed circuit board/busbar, installation situation and heat dissipation







Associated products

Counterparts

☞ 459000 0,8 1275 ☞ 459010 0,8 1260 ☞ 459010 0,8 1800
☞ 459020 0,8 1700 ☞ 459120 0,8 2000

45

458002 01




45


458002 01

Assembly tolerances for top and bottom entry


- tab dimensions 4.8 mm x 0.5/0.6/0.8 mm x length 8 mm
- larger assembly tolerances possible for lengths > 15 mm




typical mating




permissible lateral offset



permissible tilt



permissible twist




permissible combined tolerances

45


458002 01

Assembly tolerances for lateral entry


- tab dimensions 4.8 mm x 0.5/0.6/0.8 mm x length 8 mm
- larger assembly tolerances possible for lengths > 15 mm




typical mating




permissible lateral offset



permissible tilt




permissible twist



permissible combined tolerances



45 458002 01

Geometry of the mating tab contact




Material to be coordinated with Lumberg.

Packaging 458002 01 ...VP12
reel: 330 mm/100 mm/24.5 mm
leader: 408 mm, 34 empty cavities
trailer: 168 mm, 14 empty cavities



Packaging 458002 01 ...VP26
additionally with adhesive film as suction
surface for automatic placement



45

458002 01

-
- *a SMT solder area
 - *b contact point
 - *c mating from top direction
 - *d mating from lateral direction
 - *e mating from bottom direction
 - *f printed circuit board layout (example) for mating from top or lateral direction
 - *g printed circuit board layout (example) for mating from top or bottom direction
 - *h slot in the printed circuit board min. 0.5 mm wider than tab
 - *i contact tab
 - *k printed circuit board
 - *l insertion depth
 - *m dimension 1.5 mm depending on the slot in the printed circuit board

45

458002 01

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
458002 01 0,5 V12VP12	1	4000	
458002 01 0,6 V12VP12	1	4000	
458002 01 0,8 V12VP12	1	4000	

Packaging:
on reel