

45 4580 01 MP

High-current contact elements




High-current contact bush with positioning peg, in surface mount technology (SMT), mateable from top, bottom or lateral direction, for tab contacts 0.5–0.8 mm, for printed circuit boards or busbars

Approvals:

LV215

VW
80332

45 4580 01 MP



Environmental conditions

Temperature range -40 °C/+125 °C

Materials

Contact CuCr alloy, tin-plated

Mechanical data

Mating with tab contact 2.8–6.8 mm x 0.5 mm – 4580 01 MP T0,5
tab contact 2.8–6.8 mm x 0.6 mm – 4580 01 MP T0,6
tab contact 2.8–6.8 mm x 0.8 mm – 4580 01 MP T0,8
applicable for reflow soldering on printed circuit board
applicable for laser welding on a busbar or lead frame

Mating cycles ≤ 5

Insertion force tab 0.5/0.6 mm
25 N ± 15 N – top/bottom entry
18 N ± 10 N – lateral entry
tab 0.8 mm
35 N ± 15 N – top/bottom entry
18 N ± 10 N – lateral entry¹

Withdrawal force tab 0.5/0.6 mm
25 N ± 12 N – top/bottom entry
15 N ± 10 N – lateral entry
tab 0.8 mm
35 N ± 10 N – top/bottom entry
15 N ± 10 N – lateral entry¹

¹ measured with a tin-plated test tab







Electrical data (at T_{amb} 20 °C)

Contact resistance < 1 mΩ

Rated current ≤ 56 A¹

¹ depending on the connection to the printed circuit board/busbar, installation situation and heat dissipation

45 4580 01 MP




45


4580 01 MP

Assembly tolerances for top and bottom entry


- tab dimensions 4.8 mm x 0.5/0.6/0.8 mm x length 8 mm
- larger assembly tolerances possible for lengths > 15 mm




typical mating




permissible lateral offset



permissible tilt



permissible twist




permissible combined tolerances

45


4580 01 MP

Assembly tolerances for lateral entry


- tab dimensions 4.8 mm x 0.5/.06/0.8 mm x length 8 mm
- larger assembly tolerances possible for lengths > 15 mm




typical mating




permissible lateral offset



permissible tilt




permissible twist



permissible combined tolerances



45 4580 01 MP

Geometry of the mating tab contact




Material to be coordinated with Lumberg.

Packaging 4580 01 MP ... VP12
reel: 330 mm/100 mm/24.5 mm
leader: 408 mm, 34 empty cavities
trailer: 168 mm, 14 empty cavities



Packaging 4580 01 MP ... VP26
additionally with adhesive film as suction
surface for automatic placement



45

4580 01 MP

-
- *a SMT solder area
 - *b positioning peg
 - *c contact point
 - *d mating from top direction
 - *e mating from lateral direction
 - *f mating from bottom direction
 - *g printed circuit board layout (example) for mating from top or lateral direction
 - *h printed circuit board layout (example) for mating from top or bottom direction
 - *i bore hole for positioning peg
 - *k slot in the printed circuit board min. 0.5 mm wider than tab
 - *l contact tab
 - *m printed circuit board
 - *n insertion depth
 - *o dimension 1.5 mm depending on the slot in the printed circuit board

45

4580 01 MP

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
4580 01 MP T0,5V12VP12	1	4000	
4580 01 MP T0,6V12VP12	1	4000	
4580 01 MP T0,8V12VP12	1	4000	

Packaging:
on reel