


97 HA357e

Tools and harnessing machines



Semiautomatic harnessing machine for termination of RAST 2.5 Power connectors in insulation displacement technology

---

Approvals: 

---

---

**Range of application**

Connector	3570, 357099, 3575
Pole number	2-10
Pitch	5,0 mm
State of delivery of connectors	in chain
Processable conductor	discrete conductor, notched flat cable 5.0 mm

---

**Features**

Application	middle and high volume production
Stroke capacity	ca. 1000/h
Scope of functions and delivery	<ul style="list-style-type: none"> <li>- Automatic feeding of connectors</li> <li>- Verification of insertion pattern and line end position during manual insertion of conductors</li> <li>- Fixation of inserted discrete conductors by spring-loaded pressure pads until pressing</li> <li>- Automatic release of press action by control of line end position</li> <li>- Storage of insertion patterns</li> <li>- Can also be integrated into a fully automatic base machine Komax Alpha 356</li> </ul>

---

**Dimensions and supply data**

Dimensions (H x W x D)	540 mm x 690 mm x 680 mm
Weight	ca. 45 kg
Electrical supply	230 V/50 Hz
Compressed air supply	6 bar
Compressed air consumption	1 m <sup>3</sup> /1000 Steckverbinder

---

97

HA357e

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
HA357e	-		1