

97 HA357e-CA

Tools and harnessing machines



Semiautomatic harnessing machine for termination of RAST 2.5 Power connectors in insulation displacement technology (IDT), with integrated cable color detection

Approvals: 

97 HA357e-CA

Range of application

Connector	3570, 357099, 3575
Pole number	2-10
Pitch	5.0 mm
State of delivery of connectors	in chain
Processable conductor	discrete conductor, notched flat cable 5.0 mm

Features

Application	middle and high volume production
Stroke capacity	ca. 1000/h
Scope of functions and delivery	<ul style="list-style-type: none"> - Automatic feeding of connectors - Verification of insertion pattern and line end position during manual insertion of conductors - Fixation of inserted discrete conductors by spring-loaded pressure pads until pressing - Automatic release of press action by control of line end position - Cable color detection 7 + 1 - Storage of insertion patterns - Can also be integrated into a fully automatic base machine Komax Alpha 356

Dimensions and supply data

Dimensions (H x W x D)	540 mm x 690 mm x 680 mm
Weight	ca. 45 kg
Electrical supply	230 V/50 Hz
Compressed air supply	6 bar
Compressed air consumption	1 m ³ /1000 connectors

Associated products

Accessories
 HZ357-V

97

HA357e-CA

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
HA357e-CA	-		