

97 HA35e-DC

Tools and harnessing machines



Semiautomatic harnessing machine for termination of RAST 2.5 connectors in insulation displacement technology (IDT), for production of daisy chain harnesses, machine to be adapted to the application's requirements

Approvals: **CE**

97 HA35e-DC

Range of application

| | |
|---------------------------------|--|
| Connector | 3510, 3511, 3512, 3513, 3515, 3516, 3517, 3518, 351...-1, 351...-4, 3520, 3521, 3522, 3523, 352...-1 |
| Pole number | 2-20 |
| Pitch | 2.5/5.0 mm |
| State of delivery of connectors | decollated |
| Processable conductor | discrete conductor, notched flat cable 2.5/5.0 mm |

Features

| | |
|---------------------------------|--|
| Application | middle and high volume production |
| Scope of functions and delivery | - For harnessing of bus cables, possible processes and configurations on request |
| Options | - Special press die, required for 351... with side P2 being closed - Special press die, required for 3517-5 (for 1 mm printed circuit board) |

Dimensions and supply data

| | |
|----------------------------|-----------------------------------|
| Weight | ca. 45 kg |
| Electrical supply | 230 V/50 Hz |
| Compressed air supply | 6 bar |
| Compressed air consumption | 1 m ³ /1000 connectors |

Associated products

| |
|-------------|
| Accessories |
| ☑ HZ35-V |

97 HA35e-DC

| Designation | Pole Number | PU (Pieces) | MDQ (Pieces) |
|-------------|-------------|-------------|--------------|
| HA35e-DC | - | | 1 |