

Tools and harnessing machines



Semiautomatic harnessing machine for termination of RAST 2.5 connectors in insulation displacement technology (IDT), larger base machine, with integrated stations for cable color detection, keying cutting, keying testing and high-voltage test, individual upgrading possible

Approvals: (€

1 of 4 06/2023



Range of application

Connector 351..., 351...-2, 351...-4, 352..., 352...-2

Pole number 2-20 2.5/5.0 mm State of delivery of connectors in chain

discrete conductor, pre-notched ribbon cable* 2.5/5.0 mm Processable conductor

Features

middle and high-volume Application

production

Stroke capacity ca. 1200/h

Scope of functions and delivery - Automatic feeding of connectors

- Cable screen for one range of cable diameters/sections - Verification of insertion pattern and line end position during

manual

insertion of conductors - Fixation of inserted discrete conductors by spring-loaded pressure pads

until pressing

- Automatic release of press action by control of line end position - Cable color detection 7 + 1 (station CA)

keying cutting (station KC) and keying testing (station KT) - high-voltage test (station HV) Vacuum extraction device for removal of cut keying noses
Storage of insertion patterns

- Harnessing of bus cables not

Options - Special press die, required for 351... with side **P2** being closed

- Special press die, required for 3517-5 (for 1 mm printed circuit

board)

- Cable screens for additional ranges of cable diameters/sections *Conversion kit for ribbon cable (cable screen, holder, test pins,

support)

- Set of test pins for 35...-2 (20

pieces)

Dimensions and supply data

Dimensions (H x W x D) 760 mm x 1320 mm x 870 mm

Weight ca. 125 kg Electrical supply 230 V/50 Hz Compressed air supply 6 bar

Compressed air consumption 4,5 m³/1000 connectors

2 of 4 06/2023



Associated products

Accessories ☑ HZ35-V

3 of 4 06/2023



Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
HA35f-CA-KC-KT-HV			

4 of 4 06/2023