


97 HA7335e-CA

Tools and harnessing machines



Semiautomatic harnessing machine for termination of SmartSKEDD connectors in insulation displacement technology, small base machine with integrated cable color detection, limited upgrading possible

Approvals: 

97 HA7335e-CA

Range of application

| | |
|---------------------------------|--|
| Connector | 7335.. |
| Pole number | 3–13 |
| Pitch | 2,5 mm |
| State of delivery of connectors | in chain |
| Processable conductor | discrete conductor, notched flat cable* 2.5/5.0 mm |

Features

| | |
|---------------------------------|--|
| Application | middle and high volume production |
| Stroke capacity | ca. 1200/h |
| Scope of functions and delivery | <ul style="list-style-type: none"> - Automatic feeding of connectors - Cable screen for one insulation diameter/section range - Verification of insertion pattern and line end position during manual insertion of conductors - Fixation of inserted discrete conductors by spring-loaded pressure pads until pressing - Automatic release of press action by control of line end position - Storage of insertion patterns - Cable color detection 7 + 1 - Harnessing of bus cables not possible - Can also be integrated into a fully automatic base machine Komax Alpha 356 |
| Options | <ul style="list-style-type: none"> - *Conversion kit for flat cable (cable screen, holder, test pins, support) |

Dimensions and supply data

| | |
|----------------------------|---------------------------------------|
| Dimensions (H x W x D) | 500 mm x 600 mm x 700 mm |
| Weight | ca. 45 kg |
| Electrical supply | 230 V/50 Hz |
| Compressed air supply | 6 bar |
| Compressed air consumption | 1 m ³ /1000 Steckverbinder |

97

HA7335e-CA

| Designation | Pole Number | PU (Pieces) | MDQ (Pieces) |
|-------------|-------------|-------------|--------------|
| HA7335e-CA | - | 1 | 1 |