

97 HZ-M35

Tools and harnessing machines



Modular manual tongs for termination of RAST 2.5 connectors in insulation displacement technology (IDT)

Range of application

Connector	351..., 351...-2, 351...-4, 3520, 3521, 3522, 3523, 352...-2
Pole number	2-20
Pitch	2,5/5,0 mm
State of delivery of connectors	in chain
Processable conductor	discrete conductor, notched flat cable 2.5/5.0 mm

Features

Application	laboratory and sample production, harness repair
Stroke capacity	ca. 370/h
Scope of functions and delivery	<ul style="list-style-type: none"> - Fixation of inserted discrete conductors until pressing - Separation of connectors from chain during pressing - Harnessing of bus cables not possible - In transport case
Options	<ul style="list-style-type: none"> - Special press die, required for 351... with side P1 being closed - Special press die, required for 3517-5 (for 1 mm printed circuit board) - Table clamp TK-M - Connector support RS-M

Dimensions and supply data

Dimensions (H x W x D)	130 mm x 250 mm x 30 mm
Weight	ca. 1,5 kg

Associated products

Accessories
[🔗 HZ35-V](#)

97

HZ-M35

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
HZ-M35	-		1