

97 KHP35-DC

Tools and harnessing machines



Knuckle-joint press for termination of RAST 2.5 connectors in insulation displacement technology (IDT), for production of daisy chain harnesses

Range of application

Connector	351..., 351...-2, 351...-4, 3520, 3521, 3522, 3523, 352...-2
Pole number	2-20
Pitch	2.5/5.0 mm
State of delivery of connectors	decollated
Processable conductor	discrete conductor

Features

Application	low and middle volume production
Scope of functions and delivery	- Manual feeding of connectors - Fixation of inserted discrete conductors by spring-loaded pressure pads until pressing
Options	- Special press die, required for 351... with side P2 being closed - Special press die, required for 3517-5 (for 1 mm printed circuit board)

Dimensions and supply data

Dimensions (H x W x D)	430 mm x 210 mm x 350 mm
Weight	ca. 23 kg

Associated products

Accessories

[☞ HZ35-T](#)

Harnessing equipment

☞ 3510	☞ 3510-2	☞ 3511
☞ 3511-2	☞ 3512	☞ 3512-2
☞ 3513	☞ 3513-2	☞ 3515
☞ 3515-2	☞ 3516	☞ 3516-2
☞ 3517	☞ 3517-2	☞ 3517-4
☞ 3517-5	☞ 3518	☞ 3518-2
☞ 3518-4	☞ 3521	☞ 3521-2
☞ 3523	☞ 3523-2	☞ 3525

97

KHP35-DC

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
KHP35-DC	-		1