

97 KHP35-DC

Tools and harnessing machines



Knuckle-joint press for termination of RAST 2.5 connectors in insulation displacement technology (IDT), for production of daisy chain harnesses

1 of 3 11/2025

Range of application

351..., 351...-2, 351...-4, 3520, 3521, 3522, 3523, 352...-2 Connector

2-20 Pole number Pitch 2.5/5.0 mm State of delivery of connectors decollated Processable conductor discrete conductor

Features

Application low and middle volume production

Scope of functions and delivery - Manual feeding of connectors

- Fixation of inserted discrete conductors by spring-loaded pressure pads until pressing

Options - Special press die, required for

351... with side **P2** being closed - Special press die, required for 3517-5 (for 1 mm printed circuit

board)

Dimensions and supply data

Dimensions (H x W x D) 430 mm x 210 mm x 350 mm

Weight ca. 23 kg

Associated products

Accessories **☑** HZ35-T

Harnessing equipment		
♂ 3510	♂ 3510-2	₫ 3511
♂ 3511-2	₫ 3512	₫ 3512-2
₫ 3513	₫ 3513-2	₫ 3515
₫ 3515-2	₫ 3516	₫ 3516-2
₫ 3517	₫ 3517-2	₫ 3517-4
₫ 3517-5	₫ 3518	₫ 3518-2
₫ 3518-4	₫ 3521	₫ 3521-2
r₹ 3523	C₹ 3523-2	C₹ 3525

2 of 3 11/2025



97 KHP35-DC

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
KHP35-DC	-		1

3 of 3 11/2025