

36

3625 01

Freigegebene Leiter für 3625 01

Typ	Leiter		Isolierung				Material	Temp.- Bereich (°C)	Hersteller		Bezeichnung
	Querschnitt (mm ²)	Aufbau	Schlaglänge (mm)	Oberflächen- Veredelung	Durchmesser (mm)	Name			Artikelnummer		
3625 01	1,35	37 x Ø 0,215 mm	15,4	-	3 ± 0,2	PVC	+105	Alstermo	1144A	AWG 16 1596 ASKO 3,0	
3625 01	1,35	37 x Ø 0,215 mm	15,4	-	2,5 ± 0,2	PVC	+105	Alstermo	1144B	AWG 16 1596 ASKO 2,5	
3625 01	0,75	24 x Ø 0,21 mm	30	Sn	2,3+0,05/-0,10	PVC	-15/+90	KBE	35007500101905	H05V2-K 0,75 ²	
3625 01	0,78	16 x Ø 0,25 mm	50,8	-	2,74	PVC	+105	American	AWG 18 16/30 PVC Red	18ga. 16/30 BC 2/64 PVC UL 1015/1230	
3625 01	1,5	50 x Ø 0,19 mm	25	-	2,50 + 0,2	PVC	+105	Amokabel	1476	AWG 16 1569 Flex Slits	
3625 01	1,32	26 x Ø 0,254 mm	38	Sn	2,4 ± 0,10	XLPE	150	Baohing	C1307831	AWG 16	
3625 01	1,5	26 x Ø 0,25 mm	31,75	-	2,3	PVC	+105	Cable Tech	702898	AWG 16/ UL 1569/1007	
3625 01	1	32 x Ø 0,194 mm	22	Sn	2,75 ± 0,05	PVC	-40/+70	Cablana	4898	H05V-K	
3625 01	1	32 x Ø 0,194 mm	22	Sn	2,75 ± 0,05	PVC	-40/+125	Cablana	27006730	H05V2-K	
3625 01	1	32 x Ø 0,194 mm	22	Sn	2,75 ± 0,05	PVC	+70	Cablana	9055700	H05V-K	
3625 01	1	32 x Ø 0,194 +/- 0,00622 +/- 2,2	-	-	2,75 +/- 0,05	PVC	-40/+105	Cablana	7351	H05V2-K 1,00	
3625 01	1	32 x Ø 0,194 +/- 0,00622 +/- 2,2	Sn	-	2,75 +/- 0,05	PVC	-40/+105	Cablana	7352	H05V2-K 1,00	
3625 01	1,5	30 x Ø 0,244 mm	22	-	2,9	PVC	+90	Cablana	18.058	H07V2-K 1,5 mm2	
3625 01	1,5	30 x Ø 0,244 mm	22	Sn	2,95 ± 0,05	PVC	-40/+90	Cablana	2102	H07V2-K	
3625 01	1	32 x Ø 0,194 mm	22 ±	Sn	2,8 ± 0,1	PVC	-15/+90	Coficab	B52SN01006500	H05V2-K	
3625 01	1	32 x Ø 0,194 mm	22	Sn	2,8 ± 0,1	PVC	-40/+125	Coficab	B59SN01005500	A05V9-K	
3625 01	1	32 x Ø 0,194 mm	22 ±	Sn	2,8 ± 0,1	PVC	-15/+70	Coficab	B51SN01005000	H05V-K	
3625 01	1	29 x Ø 0,21 mm	39	-	2,5	PVC	+90	Coroplast	5-7022-3G1-B1-08.04.05	H05V2V2-F 3G1mm ²	
3625 01	1,3	40 x Ø 0,21 mm	44	-	3,25 ± 0,12	PVC	+105	Draka	10172130	AWG 16 AWM 1015/1011/ CSA	
3625 01	1	19 x 0,254 mm ribbon cable	21	Sn	2,6 +/- 0,1	PVC	105	Elumeg	132 11 416 1, 132 11 416 2, 132 11 416 3	LiYY- t 1 mm ² / 3,60mm	
3625 01	1	32 x 0,20 mm	30-40	-	2,75 +/- 0,08	PVC	-40/+105	Emek	31700801.W99	1,00mm ² Green/ Yellow LiY 105 C	
3625 01	1	32 x 0,20 mm	30-40	-	2,75 +/- 0,08	PVC	-40/+105	Emek	31702801.W09-W02-W07	1,00mm ² LiY	
3625 01	1,34	19 x Ø 0,30 mm	16,7	Sn	2,33 ± 0,1	Polyolefin	+125	Huber + Suhner	12522816	UL 3266/CSA AWM I A/B	
3625 01	1,5	30 x Ø 0,25 mm	34,5	Sn	2,9 ± 0,1	PVC	+105	Isomet	11411369	H07V2-K/TQ Litze 1,50 mm ²	
3625 01	1,38	44 x Ø 0,20 mm	30,8	Sn	2,35 ± 0,05	PVC	+105	KBE	4100160110200K	AWG 16 AWM 1569/1007	
3625 01	1,5	30 x Ø 0,244 mm	22	Sn	2,95 ± 0,05 VP1398/044	PVC	+90	KBE	5201500030244M	So-Ltg. 1,5 mm ² vz	
3625 01	1,5	30 x Ø 0,245 mm	32	Sn	2,95 ± 0,05	PVC	+90	KBE	3101500030244T	H07V2-K 1,5 mm ² vz	
3625 01	1,5	44 x Ø 0,20 mm	30,8	-	3,6 ± 0,1	PVC	+105	KBE	4100160000200K	UL 16 AWG AWM Style 1569	
3625 01	1,5	30 x Ø 0,26 mm	38	-	2,85 ± 0,10	PVC	+70	KBE	3401500000235E	H07V-K 1.50 mm ²	
3625 01	1,55	30 x Ø 0,244 mm	22	Sn	2,95 ± 0,05	PVC	+105	KBE	4100160110244K	16 AWG/ UL-AWM Style 1569	
3625 01	1,5	30 x Ø 0,244 mm	22	Sn	3 ± 0,1	PVC	+90	KWL	641108.86	H07V2-K 1,5 mm ² vz	
3625 01	1,5	29 x Ø 0,25 mm	18,7	-	2,8-3,4	PVC	-20/+90	Lapp	DB0026001DE	Öflex H07V2-K (AWG15)	
3625 01	1	19 x Ø 0,254 mm	18	Sn	2,85 ± 0,1	PVC	+105	Leoni	89160611A	LiYW 1,0 SN AWG 18/19 UL 1015	
3625 01	1	32 x Ø 0,20 mm	22	Sn	2,75	PVC	-40/+70	Leoni	60200840	H05V-K	
3625 01	1	32 x Ø 0,20	22	Sn	2,75 ± 0,05	PVC	-40/+90	Leoni	60A00077	H05V2-K 1x1,0 SN	
3625 01	1	32 x Ø 0,20	22	-	2,75 ± 0,05	PVC	-40/+90	Leoni	60A00078	H05V2-K 1x1,0 BL	

36

3625 01

Typ	Leiter		Isolierung				Temp.-Bereich (°C)	Hersteller			Bezeichnung
	Querschnitt (mm ²)	Aufbau	Schlaglänge (mm)	Oberflächen-Veredelung	Durchmesser (mm)	Material		Name	Artikelnummer		
3625 01	1	32 x Ø 0,194 mm	22	Sn	2,85 ± 0,1	PVC	+105	Leoni	89160612A	LiYW 1,0 SN AWG 18/32 UL 1015	
3625 01	1	32 x Ø 0,194 mm	22	Sn	2,7 + 0,05	PVC	+90	Leoni	60170030Z	H05V2-K 1,0 mm ² vz	
3625 01	1,3	26 x Ø 0,254 mm	35	Sn	2,3	PVC	-10/+105	Leoni	10.560.xxxV5310	AWM 1569 16AWG VW-1	
3625 01	1,32	26 x Ø 0,26 mm		Sn	1,55	PVC	-30/+105	Leoni	89460160	LIYW 1.32 SN AWG16/26	
3625 01	1,5	30 x Ø 0,244 mm	22	Sn	2,95 ± 0,05	PVC lead-free	+105	Leoni	89170830A	LIYW 1,5 VZ AWG 16/30 UL 1569CSATI	
3625 01	1,5	30 x Ø 0,244 mm	45	Sn	3 ± 0,1	PVC	+90	Leoni	601000040M	H07V-K 1x 1,5 mm ² SN 90C	
3625 01	1,5	30 x Ø 0,244 mm	22	Sn	3 ± 0,1	PVC	+70	Leoni	60220100Z	H07V-K 1,5 mm ² vz	
3625 01	1	32 x Ø 0,194 mm	22	Sn	2,75 ± 0,05	PVC lead-free	+70	Leoni, Poland	60200840A	H05V-K 1x1,0mm ² SN SKT	
3625 01	1	32 x Ø 0,19 mm	36	-	2,5	PVC lead-free	+70	Leoni, Turkey	68044	H05V-K 1,0	
3625 01	1	32 x Ø 0,19 mm	36	-	2,5	PVC lead-free	+90	Leoni, Turkey	72016	H05V2-K 1,0	
3625 01	1,5	30 x Ø 0,24 mm	43,5	-	2,9	PVC lead-free	+70	Leoni, Turkey	85062	H07V-K 1,5	
3625 01	1,5	30 x Ø 0,244 mm	22	Sn	2,95 ± 0,05	PVC lead-free	+90	Leoni, Turkey	60191100Z	H07V2-K 1,5 mm ² vz	
3625 01	1	19 x Ø 0,254 ± 0,01 mm		-	2,6 ± 0,10	PVC lead-free	+70	Lonsid	LD-060100002-11	60227 IEC 06 (RV)	
3625 01	1,38	41 x Ø 0,203	48	Sn	2,5 ± 0,10	PVC	-30/+105	Medi	120160	Style1007/ 1569 AWG16	
3625 01	1,5	28 x Ø 0,24 mm	33	Sn	2,9	PVC	+70	Nexans Iko	110 478XXX 12		
3625 01	1,5	28 x Ø 0,26 mm	33	Sn	2,95 ± 0,1	PVC	+70	Nexans Iko	22532700798	H05VV-F 3G1,5 mm ²	
3625 01	1,5	32 x Ø 0,23 mm	35	-	1,55	PVC	+70	Nexans Iko	S04057	H05VV-F 3G1,5 mm ²	
3625 01	1	31 x Ø 0,20 mm	32,6	-	2,4	PVC	+70	Pirelli, Turkey	79945	H05V-K 1,0 300/500 V	
3625 01	1,5	30 x Ø 0,25 mm	47	Sn	2,84	PVC	+70	Pirelli, Turkey	79921	H07V-K (Sn) 450/750 V	
3625 01	1	32 x Ø 0,194 mm	22	-	2,75 ± 0,05	PVC	-15/+90	KBE	3101000000194T	H05V2-K 1,0 mm ²	
3625 01	1	32 x Ø 0,195 mm	30	Sn	2,75 ± 0,05	PVC	+70	KBE	Muster LUM 1,0 1/00	H05V-K 1,00 mm ²	
3625 01	1	30 x Ø 0,21 mm	35	-	2,4 + 0,4	PVC lead-free	+70	KBE	3301000000190E	H05V-K 1,00 mm ²	
3625 01	1,5	26 x Ø 0,254 mm	30	Sn	2,90 +/- 0,10	PVC	+105	Lonsid	LD-101516001-11	AWG 16	
3625 01	1	28 x Ø 0,21 mm	35,2	-	2,39 ± 0,05	PVC	+70	Prysmian	9311DQ31	H05VV-F 3 X 1 mm ²	
3625 01	1	31 x Ø 0,20 mm	33	-	2,40 + 0,40	PVC lead-free	+70	Prysmian, Turkey	2006-VS-70-100	H05V-K 1.00 mm ²	
3625 01	1,5	29 x Ø 0,25 mm	36	-	2,80 + 0,20	PVC lead-free	+90	Prysmian, Turkey	2006-VS-90-150	H07V2-K 1.5 mm ²	
3625 01	1,5	29 x Ø 0,25 mm	36	-	2,80 + 0,20	PVC lead-free	+70	Prysmian, Turkey	2006-VS-70-150	H07V-K 1.50 mm ²	
3625 01	1	32 x Ø 0,193 mm	27 ± 1	-	2,47 ± 0,1	PVC	-20/+70	Salcavi	R13810	H05V-K S	
3625 01	1,5	30 x Ø 0,244 mm	20	Sn	2,85 ± 0,1	PVC	+70	Salcavi	R10882	H07V-K 1 x 1,50 mm2	
3625 01	1,50	30 x Ø 0,243 mm	28 ± 2	Sn	2,8 ± 0,1	PVC	-20/+70	Salcavi	R13269	H07V-K 1x 1,5mm ²	
3625 01	1,5	30 x Ø 0,243 mm	28 ± 2	Sn	2,8 ± 0,1	PVC	-20/+70	Salcavi	R13270	H07V-K 1x 1,5mm ²	
3625 01	1	32 x Ø 0,20 +/- 0,010	20-30	-	2,6 ± 0,10	PVC	+70	Baohing	SWE-VDEBH-276-H4W	H05V-K 1,0mm ²	
3625 01	1,5	30 x Ø 0,25 mm		-	3,05 +0,05/-0,10	PVC	+70	Baohing	SWE-VDEBH-279-H4W	H07V-K	
3625 01	1	32 x Ø 0,20 mm	36	Sn	2,50 ± 0,10	PVC	+180	Silitherm	ST0403\$	SIF-VDE	
3625 01	1,34	19 x Ø 0,30 mm	50	Sn	2,4	Polyolefin	+145	Studer	Betatherm 145 AWG 16	AWM 3266/ CSA-CSL 1252	
3625 01	1,5	26 x Ø 0,254 mm	22 33	Sn	3,0 ± 0,05	PVC	+105	Baohing	ULSBH-267T/3-MZ	AWG 16	
3625 01	1	32 x Ø 0,193	22 +/- 2	Sn	2,75 ± 0,1	PVC	-40/+105	Vercavi	HD1100RO00S4	H05V2-k 1 x 1,0mm ²	
3625 01	1	32 x Ø 0,193 mm	41,9	-	2,5 ± 0,1	PVC	-15/+105	Vercavi	HH1100----0C	FR3/2 HAT 105 SEZ 1x1,0	

36

3625 01

Typ	Leiter		Isolierung				Hersteller			Bezeichnung
	Querschnitt (mm ²)	Aufbau	Schlaglänge (mm)	Oberflächenveredelung	Durchmesser (mm)	Material	Temp.-Bereich (°C)	Name	Artikelnummer	
3625 01	1	32 x Ø 0,193 mm	29,4	-	2,55 ± 0,1	PVC	-15/+105	Vercavi	HH1100VEGI03	FR3/2 1,00 mm ²
3625 01	1	32 x Ø 0,193	22 +/- 2	-	2,75 ± 0,1	PVC	-40/+105	Vercavi	HD1100VEGI04	H05V2-K 1 x 1,0mm ²
3625 01	1	32 x Ø 0,193 mm	29,4	Sn	2,55 ± 0,1	PVC	-15/+105	Vercavi	HH1100RO00S3	FR3/2 1,00 mm ²
3625 01	1	32 x Ø 0,194 mm ± 0,006	22 ± 2,2	Sn	2,75 ± 0,05	PVC	-5/+90	Leoni	60A00077A	H05V2-K 1x1,0 SN
3625 01	1	32 x Ø 0,21 mm	32	-	2,4-2,8	PVC	-15/+90	Coficab	08IEC0100XXYY	H05V2-K
3625 01	1	32 x Ø 0,21 mm	≤ 65	-	2,4-2,8	PVC	-15/+90	Coficab	52KS0100XXYY	H05V2-K 1 mm ²
3625 01	1	32 x Ø 0,194 mm	22 ± 10%	-	2,75 ± 0,05	PVC	-5/+90	Leoni	60A00078A	H05V2-K 1 x1,0 BL
3625 01	1	57 x Ø 0,15 mm	35	-	2.4	PVC	60	Leoni	5001478/5001479	H05VV-F 3G1,00
3625 01	1	32 x Ø 0,194 mm ± 0,006	35 ± 10 %	-	2,6 ± 0,2	PVC	-40/+70	Cablana	16.006.70x.2	H05V-K 1,00
3625 01	1	32 x Ø 0,20 mm	15	-	2,50 ± 0,1	Silicone	180	BLF	4J/ 2843...	EI2-FG4/2
3625 01	1	32 x Ø 0,20 mm	15	-	2,50 ± 0,1	Silicone	130	BLF	4J/ 2843135300/ 01	SIL/ 0100F 1,00 mm ²
3625 01	1	32 x Ø 0,194 mm ± 0,006	22	Sn	≤ 1,50	PVC	-15/+70	KBE	3101000030194E	H05V-K 1,00 mm ²
3625 01	1,25	19 x Ø 0,29 mm	19	Sn	2,92 ± 0,05	Silicone	200	Rowe	SW16WS3322	AWM Style 3322
3625 01	1,32	26 x Ø 0,26 mm	22 ± 2	Sn	2.35	Soft PVC	105	Leoni	89460162	AWG 16/ 26
3625 01	1,32	26 x Ø 0,254 mm	51	Sn	2,4 ± 0,10	Soft PVC	105	Baohing	ULBH-328T/3-KBL	AWG 16/ 26
3625 01	1,32	26 x Ø 0,254 mm	51	Sn	2,40 ± 0,10	PVC	105	Baohing	102010140160 XX	AWG 16 UL 1569

Copyright Lumberg Holding © 2026