

Approved Cables for 3625-1 S03

Type	Conductor			Surface finishing	Insulation			Manufacturer		
	Cross Section (mm ²)	Construction	Length of Lay (mm)		Diameter (mm)	Material	Temp. Range (°C)	Name	Designation	Description
3625-1 S03	1	19 x Ø 0,26 mm	10	Sn	2,5 ± 0,1	Silicone	+180	Cet	999010502016A	
3625-1 S03	1	19 x Ø 0,26 mm	10	Sn	2,5 ± 0,1	Silicone	+180	Cet	999010504006A	
3625-1 S03	1	19 x Ø 0,26 mm	10	Sn	2,5 ± 0,1	Silicone	+180	Cet	999010505013A	
3625-1 S03	1	19 x Ø 0,26 mm	10	Sn	2,5 ± 0,1	Silicone	+180	Cet	999010509006A	
3625-1 S03	0,75	24 x Ø 0,21 mm	30	Sn	2,3 +0,05/-0,10	PVC	-15/+90	KBE	35007500101905	H05V2-K 0,75 ²
3625-1 S03	1	19 x Ø 0,26 mm	10 ± 2	Sn	2.5	Silicone	180	BLF	51/ 2843 .. 53P7/01	Silicone 1,00 mm ²

Connector systems with insulation displacement and crimp technology require suitable cables and accurate processing. In order to assure safe function of the connectors they must be processed with Lumberg harnessing equipment (series 97), according to Lumberg harnessing instructions, using cables approved by Lumberg. Do not hesitate to contact us if you have any questions!

The cables listed here have been tested in the laboratory and have been approved suitable for the specified connector type. Lumberg cannot assume warranty for possible modifications on the part of the cable manufacturer. It is the user's responsibility to ensure the compatibility of the chosen components and their appropriateness for the intended application.

01/2019