

36

3647-1

Approved Cables for 3647-1 S03

Type	Conductor		Length of Lay (mm)	Surface finishing	Insulation			Manufacturer		Description
	Cross Section (mm ²)	Construction			Diameter (mm)	Material	Temp. Range (°C)	Name	Designation	
3647-1 S03	1,5	30 x Ø 0,244 mm	22	Sn	2,95 ± 0,05	PVC	+70	KBE	31015000KBE30244EBR	H07V-K 1,50
3647-1 S03	1	19 x Ø 0,26 mm	10	Sn	2,5 ± 0,1	Silicone	+180	Cet	999010502016A	
3647-1 S03	1	19 x Ø 0,26 mm	10	Sn	2,5 ± 0,1	Silicone	+180	Cet	999010504006A	
3647-1 S03	1	19 x Ø 0,26 mm	10	Sn	2,5 ± 0,1	Silicone	+180	Cet	999010505013A	
3647-1 S03	1	19 x Ø 0,26 mm	10	Sn	2,5 ± 0,1	Silicone	+180	Cet	999010509006A	
3647-1 S03	1,38	41 x Ø 0,203 mm	48	Sn	0,38	PVC	-40/+105	Medi	120160 ...	AWG 16
3647-1 S03	1	19 x Ø 0,26 mm	10 ± 2	Sn	2.5	Silicone	180	BLF	51/ 2843 ... 53P7/01	Silicone 1,00 mm ²
3647-1 S03	1	19 x Ø 0,26 mm	10 ± 2	Sn	2.5	Silicone	180	BLF	51/ 2843 ... 53P7/01	Silicone 1,00 mm ²
3647-1 S03	1	19 x Ø 0,25 +/- 0,005	12,9	-	3,6 +/- 0,15	PVC	-25/+90	Eldra	908 08	LiYwYw 1,00mm ²

Copyright by Lumberg Holding © 2024