

73

733500

Approved Cables for 733500

Type	Conductor		Length of Lay (mm)	Surface finishing	Insulation			Manufacturer		
	Cross Section (mm ²)	Construction			Diameter (mm)	Material	Temp. Range (°C)	Name	Designation	Description
733500	0,35	7 x Ø 0,26 mm	25	-	1,30 ± 0,1	TPE-E	-40/+150	Gebauer & Griller	68534	FLR13Y-A 0,35 mm ²
733500	0,38	12 x Ø 0,194 mm ± 0,006	15	-	1,4 ± 0,05	PVC	-15/+70	KBE	5000380120198E	LiY 0,38 mm ²
733500	0,35	12 x Ø 0,21 mm	25	Sn	1,40 -0,2	PVC	-40/+105	KBE	1000350110195A	FLRY 0,35 mm ²
733500	0,38	12 x Ø 0,194 ± 0,006 mm	15	-	1,40 ± 0,05	PVC	+5/+70	Leoni	88200132Z	LiY 0,38 mm ²

Connector systems with insulation displacement and crimp technology require suitable cables and accurate processing. In order to assure safe function of the connectors they must be processed with Lumberg harnessing equipment (series 97), according to Lumberg processing instructions, using cables approved by Lumberg. Do not hesitate to contact us if you have any questions!

The cables listed here have been tested in the laboratory and have been approved suitable for the specified connector type. Lumberg cannot assume warranty for possible modifications on the part of the cable manufacturer. It is the user's responsibility to ensure the compatibility of the chosen components and their appropriateness for the intended application.

11/2021