

73

733500

## Approved Cables for 733500

Type	Conductor		Length of Lay (mm)	Surface finishing	Insulation			Manufacturer		
	Cross Section (mm <sup>2</sup> )	Construction			Diameter (mm)	Material	Temp. Range (°C)	Name	Designation	Description
733500	0,35	7 x Ø 0,26 mm	25	-	1,30 ± 0,1	TPE-E	-40/+150	Gebauer & Griller	68534	FLR13Y-A 0,35 mm <sup>2</sup>
733500	0,38	12 x Ø 0,194 mm ± 0,006	15	-	1,40 ± 0,05	PVC	-15/+70	KBE	5000380120198E	LiY 0,38 mm <sup>2</sup>
733500	0,35	12 x Ø 0,21 mm	25	Sn	1,40 -0,2	PVC	-40/+105	KBE	1000350110195A	FLRY 0,35 mm <sup>2</sup>
733500	0,36	12 x Ø 0,194 mm	15	-	1,40 ± 0,05	PVC	-5/+70	Leoni	88200132Z	LiY 1 x 0,38 mm <sup>2</sup> BL
733500	0,25	7 x Ø 0,2 mm	12	Sn	1,42-1,48	PVC	-15/+70	Prysmian	20143789	Protodur LiY 0,25 mm <sup>2</sup>

Copyright by Lumberg Holding © 2024